



NOTES:

1. All steelwork and fixings to be galvanised.
2. All concrete outbreak to be patched to Spec. B15.
3. All plates to be seated on 25 nom. grout.
4. All welds to be 6mm C.F.W. or full penetration butt welds, u.n.o.
5. Post spacing to be typically 1m
6. 1.5m long concrete taper to bring kerb face 250mm behind barrier at 200mm above shoulder surface.

BARRIER TYPE	H	BEAM TYPE
LOW	720 ±20	W BEAM
REGULAR	805 ±20	THREE BEAM

No.		AMENDMENTS		CHECKED	DATE	APPROVED		APPROVED		DATE ACCEPTED	
1		Kerb Taper Added		GKR	15/9/05	GKR		G ROBERTS		29/9/04	
			DRAFTING			DESIGN			DEPARTMENT OF INFRASTRUCTURE, ENERGY AND RESOURCES, TASMANIA		
			DRAWN	DATE	DESIGNED	DATE	BRIDGE FENCE TYPE 2			FROM LINK NO. / INSTANCE	TO LINK NO. / INSTANCE
			DT		GDM					CONTRACT No.	SHEET No.
			CHECKED	DATE	RECOMMENDED/CHECKED	DATE				DRG No.	3402-4/P73-1
			GKR	15/9/05	G ROBERTS	29/9/04					